

## ZH350ST

Compact short throw Full HD laser projector









- Bright Full HD 1080p DuraCore laser projector -3500 lumens and IP6X certified
- Compact and short throw lens for easy installation
  360-degree and portrait projection
- Reduced power consumption for a long life span -DuraCore laser technology delivers 30,000 hours maintenance free laser light source
- External power supply More reliability, portability and energy efficiency



The ZH350ST is one of Optoma's most compact and hassle-free Full HD 1080p DuraCore laser projectors to date. Designed for maintenance-free continuous operation, this 3500-lumen projector delivers powerful image performance with flexible installation features and extensive connectivity options in a sleek, compact form factor, up to 34% smaller than previous Optoma models.<sup>1</sup>

An added benefit, the ZH350ST features an external power supply offering more reliability, portability and energy efficiency.

## **Specifications**

EAN: 5055387666795, Colour: White

UPC: 796435 44 657 4, Colour: White

Display/image

Display technology DLP™

Resolution 1080p Full HD (1920x1080)

**Brightness** 3.500 lumens Contrast ratio 300,000:1 2,000,000:1 Contrast ratio - dynamic 16:9 Native aspect ratio 4:3 16:9 16:10 Aspect ratio - compatible

Keystone correction -

+/-30°

Keystone correction - vertical +/-30° Has vertical auto keystone Yes

correction

horizontal

Displayable colours (millions) 1073.4 Horizontal scan rate 15 ~ 140Khz Vertical scan rate 24 ~ 120Hz Uniformity 75%

0.76m ~ 7.62m (30" ~ 300") diagonal Screen size

Lamp info Light source type LASER life 30,000 hours

Optical Throw ratio

0.496:1 Projection distance (m) 0.3m - 3.3m Zoom type Fixed Focal length (mm) 7.51 116% Native offset

Connectivity

Connections Inputs 2 x HDMI 2.0

Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A

Control 1 x RS232

General Noise level (typical)

Noise level (max)

32dB 34dB

PC compatibility FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility

NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4,25/4,4MHz 480i/p, 576i/p.

720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)

Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) 3D compatibility 720p50 / 60

Full 3D

3D

Security Security bar, Kensington Lock, Password protected interface IP rating

OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi

Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese Yes

24/7 operation 360° operation

0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m Operating conditions

Card style Remote control Speaker count Watts per speaker 15W In the box

AC power cord Remote control 1x CR2025 battery Basic user manual

Input lag 8.60ms UHDCast Pro Optional wireless models

Power

100V ~ 240V, 50-60Hz Power supply

<0.5W Power consumption (standby) 98W Power consumption (min) Power consumption (max) 139W

Weight and dimensions

Dimensions (W x D x H) mm 274 x 216 x 114 Gross weight 4.2 kg Net weight 3 ka





